

Agasthya 2021 Series Conductivity Sensor Model BI1330-S-T-K0.1



(Note : This is reference image)

Features:

- Measuring specific Conductivity/TDS of aqueous solutions is becoming increasingly important for determining impurities in water
- Conductivity sensor works on Measurement principle of Electrode method (2-electrode type)
- Conductivity sensor is designed in such a way that can handle these measurements even in extreme conditions
- Conductivity Sensor Ensures optimal performance in monitoring conductivity level
- Easy to install for various online monitoring systems

Technical Specification

General	Measurement Range: 0-2 mS Cell Constant: 0.1 Electrode material: Two Electrode probe
Physical	Sensor Material: SS316L Cable Length: Standard 5m cable, Customize length available
Environmental	Temperature range: (-)10 - 150°C Temperature Compensation: Pt100
Performance	Process Connection: 3/4" NPT IP Rating: IP68
Application	Effluent Groundwater Pharma Application Chemical Industry Petroleum Application

Head Office :

409, 4th Floor, Avior (Nirmal Galaxy),
Next to Deep Mandir, Opp. Johnson & Johnson,
L.B.S. Marg, Mulund (W), Mumbai - 400080.

Manufacturing Unit :

201, 207, 208, G Wing, Udyog Bhavan No.: 2,
Plot No.: K-3, Additional Ambarnath MIDC,
Ambarnath-East-421506, Dist.: Thane,
Maharashtra.

Phone : + 91-22-25916858, 25916916 Cell : +91 8693050520

Email : sales@bhoomiltd.com, service@bhoomiltd.com

Website : www.bhoomiltd.com